

RECEIVED
CENTRAL FAX CENTER

AUG 20 2007

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) An elongated load-bearing support with load-bearing strands each having a plurality of fibers, the strands being surrounded by a sheath, the strands comprising:

a plurality of load-bearing fibers formed of a base material being in a first phase; and
a reinforcing material being in a second phase and being distributed in said base material
whereby said reinforcing material increases a modulus of elasticity of the strands
in a longitudinal direction of said fibers for supporting at least one of an elevator
car and an elevator counterweight.

2. (Previously Presented) The support device according to claim 1 wherein the strands having said plurality of fibers are formed into one of a cable and a belt.

3. (Currently Amended) The support device according to claim 1 wherein said base material is one of steel, plastic, synthetic compositions, aramid and Zylon and said reinforcing material increases a modulus of elasticity of each of said fibers in a longitudinal and/or radial direction of said fibers.

4. (Original) The support device according to claim 1 wherein said reinforcing material has a higher modulus of elasticity than a modulus of elasticity of said base material.

5. (Original) The support device according to claim 1 wherein said reinforcing material is arranged and distributed in said base material in the form of at least one of long fibers, short fibers, spheres, grains, capsules, discs and plates forming a matrix.

6. (Original) The support device according to claim 1 wherein said plurality of fibers is surrounded by a sheath.

16615

7. (Currently Amended) An elongated load-bearing elevator support device with load-bearing strands each having a plurality of fibers, the strands being surrounded by a sheath, the strands comprising:

- a plurality of fibers formed of a base material being in a first phase; and
- a reinforcing material being in a second phase and being distributed in said base material whereby said reinforcing material increases a modulus of elasticity of the strands in a longitudinal direction of said fibers for supporting at least one of an elevator car and an elevator counterweight.

8. (Currently Amended) The elevator support device according to claim 7 wherein said first phase base material is one of steel, plastic, synthetic compositions, aramid and Zylon, and said second phase reinforcing material increases a modulus of elasticity of said fibers in a ~~longitudinal and/or~~ radial direction of said fibers.

9. (Original) The elevator support device according to claim 7 wherein said reinforcing material has a higher modulus of elasticity than a modulus of elasticity of said base material.

10. (Original) The elevator support device according to claim 7 wherein said reinforcing material is arranged and distributed in said base material in the form of at least one of long fibers, short fibers, spheres, grains, capsules, discs and plates forming a matrix.

11. (Currently Amended) A method of producing an elongated elevator load-bearing support device comprising the steps of:

- a. producing a plurality of fibers formed of a base material being in a first phase and reinforced by a reinforcing material being in a second phase and being distributed in said base material;
- b. forming a plurality of load-bearing strands with said fibers; and
- c. surrounding said strands with a sheath to form the support device whereby the reinforcing material increases a modulus of elasticity of the strands in a longitudinal direction of the fibers for supporting at least one of an elevator car and an elevator counterweight.

12. (Original) The method according to claim 11 including a step of selecting the base material from steel, plastic, synthetic compositions, aramid and Zylon.

13. (Original) The method according to claim 11 including a step of selecting the reinforcing material to have a higher modulus of elasticity than a modulus of elasticity of the base material.

14. (Currently Amended) The method according to claim 11 including a step of selecting the reinforcing material to increase a modulus of elasticity of the fibers in a ~~longitudinal and/or~~ radial direction of the fibers.

15. (Original) The method according to claim 11 including a step of forming the reinforcing material as particles in the form of at least one of long fibers, short fibers, grains, capsules, spheres, discs and plates.